

AD-N3D8	N Plug To MCX Jack	50Ω																		
<p>Typical VSWR</p> <table border="1" style="margin: auto; border-collapse: collapse;"> <thead> <tr> <th>Part Number</th> <th>1 GHz</th> <th>2 GHz</th> <th>3 GHz</th> <th>4 GHz</th> <th>5 GHz</th> <th>6 GHz</th> <th>7 GHz</th> <th>8 GHz</th> </tr> </thead> <tbody> <tr> <td>AD-N3D8</td> <td>1.05</td> <td>1.05</td> <td>1.08</td> <td>1.16</td> <td>1.31</td> <td>1.31</td> <td>1.31</td> <td>1.31</td> </tr> </tbody> </table>			Part Number	1 GHz	2 GHz	3 GHz	4 GHz	5 GHz	6 GHz	7 GHz	8 GHz	AD-N3D8	1.05	1.05	1.08	1.16	1.31	1.31	1.31	1.31
Part Number	1 GHz	2 GHz	3 GHz	4 GHz	5 GHz	6 GHz	7 GHz	8 GHz												
AD-N3D8	1.05	1.05	1.08	1.16	1.31	1.31	1.31	1.31												
Parts	Material	Plating (Micro-inch)																		
Contact Pin(Jack)	Beryllium Copper	Gold 10 Over Nickel 50 Over Copper 50																		
Insulator	Teflon																			
Contact Pin(Plug)	Brass	Gold 10 Over Nickel 50 Over Copper 50																		
Body(N)	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50																		
Body(MCX)	Brass	Gold 5 Over Nickel 50 Over Copper 50																		
Renber Ring	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50																		
Gasket	Silicone																			
Contact Body	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50																		
Coupling Nut(N)	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50																		
Weight: 28.33 g																				

Notice: JYEBAO reserves the right to make modifications deemed appropriate.